5-14-2018: File reviewed, more current MSDS/SDS not available. JMC

## MSDS for #02902 - INCREDIBLE NIB

:

3

|        |  |  |  | ·  |  |
|--------|--|--|--|--|--|
|        | (aunu andur  | * Incredi  | HE NIB Frisket   | kit *  | 02902-0002   |
|        | ATERIAL SPETY<br>USHA Hazard Com<br>Standard (29 CF  | 18 2008<br>DATA SHEET<br>munication<br>R 1910.1200   |  | Printed on 7   | SHA FORMS 20 AND 174<br>Department of Labor<br>/30/92 at 15:06:54  |
|        | Material/Produc<br>Incredible Whit<br>Color White Lig  | t Identity<br>e Mask Liquid<br>uid I   | Frisket<br>D # N∕A   | N  | 4 Rev. No. A<br>6-89 Certified<br>tion Product<br>y Not known to<br>be regulated   |
|        | SECTION I  | MANUFACTURE  | R'S NAME AND L   | DCATION  | 00312-1004   |
|        | Manufact. Name<br>Address line 1<br>Address line 2<br>Address line 3<br>Info. Tel. No.<br>Prep. Date             | Graphic Art:<br>19499 Miles<br>Cleveland, (<br>USA Emerg.<br>(800) 447-2:<br>7/23/92                               | Systems Inc.<br>Road<br>DH 44128<br>Tel. No. (800<br>349<br>Cont<br>Tit                                  | 468-6942 USA<br>act Lawrence<br>le President   | Ratz Current per Brenk<br>24 mile 212 7/17/4<br>CONTENT INFORMATION  |
|        |  |  |  |  | STEL & COMP<br>N/L < 100%<br>35 ppm < 5 %  |
|        | This is a profese<br>with a small qua<br>expected hazards<br>excessive heat,<br>SECTION III                      |  | and out out out out the set of the set of the set of the   |  | polymer solution<br>luated for<br>al artists. Avoid<br>ventilation.  |
|        | -  | Not App<br>N/K<br>Water-like<br>Water-like<br>nia odor   | Deg. F (Cel)<br>Deg. F (Cel)<br>Appea  | Spec. Grav<br>(H2O=1)<br>Vapor Density<br>Water Solubil<br>rance Hilky Aq                                      | Less than 1<br>Same as Water<br>ity Soluble<br>ueous Liquid  |
| -      | Flash Point Not<br>Lower Flam. Limi<br>Exting. Medium<br>Specialized Fire<br>Fighting Proc.                      | App. Deg. F.<br>t Not App.<br>Water spray, d<br>Burning dry 1<br>Wear self-con<br>clothing to pr<br>combustion fur | (Cel) Flash P<br>ry chemical, Co<br>itex produces<br>cained breathin<br>revent exposure<br>tes. No unusu | t. Method Not<br>Upper Flam. L<br>dense black cloud<br>of apparatus and<br>to usual and d<br>al toxic gases to | App.<br>imit Not App. %<br>uds of smoke. 2<br>d protective<br>axpected 4<br>are expected. 5<br>d; dried rubber 4                           |
| l      | Inusual Fire &<br>Explosion Hazard   | Expect the usu   | al toxic gases   | to be produced<br>black smoke.   | 1; dried rubber <u>V</u>   |
| OTH IN | ECTION V<br>(Unstable)<br>(table (ves/no)<br>(Stable)<br>(ncompat. (Avoid)<br>az. Decomp.(y/n)<br>ond. to Avoid. | Yes<br>Solvents, a<br>No   | Conditions Ex<br>to avoid<br>cids, metals,<br>Haz. Polym.<br>other organic<br>produce nitrog             | cessive Heat; f<br>salts may coagu<br>(yes/no) No<br>material, comb<br>en oxides, carb                         | -  |
| i g    |  |  |  |  |  |
|        | Re   | Spirable Fractionsure Limit  | on R<br>EL ACC<br>ACC  | IH Threshold Li<br>O be reliable,<br>of this inform  | iling Value C<br>Determined N/D<br>Listed N/L<br>nown UNXWN<br><u>mit Value TLV</u><br>The user should<br>ation for any<br>Reg. TM, ACGIH) |
|        |  |  |  |  |  |
|        |  |  |  |  |  |

Page 1 of 4

•

.

MSDS for #02902 - INCREDIBLE NIB

٠,

ļ

? ? |

1

1

·

÷.

|  |  |  | ·                        |
|--|--|--|--------------------------|
| : · · ·  |  | -  |                          |
| Standard (29 CFR 1)  |  | Printed on 7/30/92 at  | nt of Labor              |
| Material Identity<br>Color White   | Incredible White Ka<br>Liquid  | isk Liquid Frisket<br>ID # N/A   |                          |
| SECTION VI .   | HEALTH HAZARD DATA   |  |                          |
| avoi<br>ligu   | d breathing mist. Us   | avoid inhaling mist if spra<br>gest. Not likely to be inge<br>ty uses of the product; amm<br>irritate eyes if vaporized<br>sprayed, use adequate cros<br>or applied by air brush or<br>e a NIOSH approved mask sui | table for                |
| NTP Carcinogen N/L<br>Signs/Symptoms None<br>of Exposure   | IARC Carcinoge<br>expected but eye irr   | n N/L OSHA Carcinoge<br>itation may occur.   | n N/L                    |
| Medical Conditions   | None known. Avoid w<br>is possible.  | earing contact lenses if ey  | e contact                |
| First Ald II conta<br>Measures 15 minut<br>contact,  | ct with eyes occurs,<br>es; contact a physici<br>wash with water.  | rinse with lukewarm, clean v<br>an if irritation occurs. S   | water for<br>kin         |
| SECTION VII -  | PRECAUTIONS FOR SAFE   |  |                          |
| Spill<br>Waste Disp  | Contain and collect<br>Observe all federal,  | for disposal.<br>state and local laws concer   | rning ·                  |
| Precautions<br>Other Precautions   | None known; use caut:<br>None known.   | state and local laws concernt.<br>nt.<br>ion as spill area may be sli  | Lppery.                  |
| SECTION VIII   | CONTROL MEASURES   |  |                          |
| Resp. Protect.   | Not usually required<br>mists should be worn<br>large quantity.  | but a suitable mask for aer<br>if material is to be spraye   | osls and<br>d in         |
| Local Exhaust<br>Spec. Local. Exh.<br>Mech. Exhaust<br>Other Mech. Exhaust<br>Protect. Gloves<br>Eye Protect<br>Protect. Clothing<br>Work Practices                            | Not usually required<br>None usually required<br>None required except<br>None<br>Vinyl or rubber glove<br>Not required for ordi<br>None specifically red | es.<br>.nary uses of this product<br>fuired; artist smock suggest<br>bractice for the handling of  | ed.<br>artist            |
| LABEL STATEMENTS<br>Acute Toxicity Sig<br>Acute Phrase 1<br>Acute Phrase 2<br>Acute Phrase 3<br>Chronic Toxicity C<br>Chronic Phrase 1<br>Chronic Phrase 3<br>Chronic Phrase 3 | nal Word 1 No Acute<br>DO NOT TAKE INTER<br>KEEP OUT OF REACH  | Health Labeling Required<br>NALLY. AVOID CONTACT WITH<br>OF CHILDREN.<br>additional information.<br>nic health labeling require  | EYES.                    |
| ASTM D4236 Com<br>Certification Assur  | plies with ASTM D4236<br>ance  | -89  |                          |
| Confirm all informat   | <u>ion prior to use</u>  | Ceiling Val  | lue C                    |
| Abbreviations: Not A<br>Not Ki   | oplicable N/A. Not P<br>Nown N/K<br>Cable Fraction R   | rlammable N/F Not Determi<br>Not Listed<br>Unknown   | ined N/D<br>N/L<br>UNKWN |
| Permissible Exposu   | re Limit PEL<br>Skep from sources judo   | ACGIH Threshold Limit Valu   | E TLV                    |
| intention or purpose   | No other warranty  | lity of this information for<br>is given. (TLV Reg. TM   | , ACCTH ) <sup>14</sup>  |
|  |  |  |                          |
|  |  |  |                          |

Í.

.

:

.

•

i .

. .....

MSDS for #02902 - INCREDIBLE NIB

ł

÷

ī.

ł

| White Liquid  | dentity<br>ask Liquid Frisket<br>N/A  | Seq. No. 4<br>ASTM D4236-89<br>Certification<br>Regulatory<br>Status | Rev. No. A<br>Certified<br>Product<br>Not known to<br>be regulated |
|---|---|--|--|
| Address line 1<br>Address line 2<br>Address line 3<br>Info. Tel. No.            | Graphic Arts Systems Inc.<br>19499 Miles Road<br>Cleveland, OH 44128<br>JSA Emerg. Tel. No. (800)466<br>(800) 447-2349 Contact<br>7/23/92 Title |  |  |
| Conformity Phrase   | REQUIRED LABEL<br>Complies with ASTH D4236-89   | · •  |  |
| Acute Signal Word<br>Acute Phrase 1<br>Acute Phrase 2<br>Acute Phrase 3         | No Acute Health Labeling Re<br>DO NOT TAKE INTERNALLY. AV<br>KEEP OUT OF REACH OF CHILDR<br>Refer to MSDS for additiona                         | COID CONTACT WITH  | EYES.  |
| Chronic Signal Word<br>Chronic Phrase 1<br>Chronic Phrase 2<br>Chronic Phrase 3 | No chronic health labeling  | required .   |  |
| Mis'c Warning Word  | KEEP OUT OF REACH OF CHILDR   | EN   |  |



Page 4 of 4

