MATERIAL SAFETY DATA SHEET

ISOPROPYL ALCOHOL 99%

PADDOCK LABORATORIES, INC.

EMERGENCY ASSISTANCE:

3940 QUEBEC AVENUE NORTH

CHEMTREC 800-424-9300

MINNEAPOLIS, MINNESOTA 55427

PHONE: (763)-546-4676

PADDOCK TECH. ASST. 800-328-5113

DATE PREPARED: 10-18-91

BY: Patrick L. Johnson

REVISED: 01-16-03

BY: Eric Randall

SECTION 1 - PRODUCT IDENTIFICATION AND HAZARDOUS COMPONENTS

PRODUCT NAME: Isopropyl Alcohol 99%

SYNONYMS: Isopropanol, Isopropyl Alcohol Anhydrous

MOLECULAR FORMULA: C₃H₈O

MOLECULAR WEIGHT: 60.09

CHEMICAL NAME: 2-Isopropanol

CHEMICAL FAMILY: Aliphatic alcohol

INGREDIENT (CAS #)

OSHA PEL ACGIH TLV

Isopropyl alcohol (67-63-0)

400 ppm

400 ppm

SECTION 2 - PHYSICAL AND CHEMICAL CHARACTERISTICS

BOILING POINT:

82°C

VAPOR PRESSURE: 37 mm Hg @ 20°C

MELTING POINT: N/A

VAPOR DENSITY: 2.1 (air = 1)

SPECIFIC GRAVITY:

0.783 - 0.787

99

EVAPORATION RATE: 1.70

(WATER = 1)

 $(BUTYL\ ACETATE = 1)$

WATER SOLUBILITY:

Freely soluble

WATER REACTIVE: No

APPEARANCE AND ODOR: Clear, colorless, volatile, flammable liquid; characteristic odor.

SECTION 3 - FIRE AND EXPLOSION DATA

FLASH POINT (METHOD): 11.7°C (CC)

AUTOIGNITION TEMPERATURE: 455.6°C

FLAMMABLE LIMITS: LOWER: 2.5% (v/v)

UPPER: 12% (v/v)

EXTINGUISHING MEDIA: Water spray, carbon dioxide, chemical foam.

SPECIAL FIRE FIGHTING PROCEDURES: Fire fighters should wear full protective gear including selfcontained breathing apparatus. Water spray may be used to minimize vapors and cool containers exposed to neat and flame, however, caution must be used to avoid spreading burning liquid.

UNUSUAL FIRE AND EXPLOSION HAZARDS: This material is extremely flammable and may be ignited by heat, spark, flame or static discharge.

SECTION 4 - REACTIVITY HAZARD DATA

STABILITY: Stable (X) Unstable ()

INCOMPATIBILITY (MATERIALS TO AVOID): Anhydride, isocyanate, acetylaldehyde, chlorine, ethylene oxide, hydrogen peroxide.

HAZARDOUS DECOMPOSITION PRODUCTS: As with any organic compound, this material may produce toxic carbon monoxide and carbon dioxide fumes if heated to decomposition.

HAZARDOUS POLYMERIZATION: May Occur () Will Not Occur (X)

SECTION 5 - HEALTH HAZARD DATA

TOXICITY:

 LD_{50} : Oral (rat) = 5.8 gm/kg

OSHA IDLH: 20,000 ppm ACGIH STEL: 500 ppm

CARCINOGEN LISTED BY:

Yes() No(X) NTP

IARC Yes() No(X) **OSHA** Yes() No(X)

Yes() No(X) Other

ROUTES OF ENTRY: Inhalation, ingestion, absorption.

SIGNS AND SYMPTOMS OF OVEREXPOSURE:

INHALATION: May cause irritation of the respiratory tract, headache, dizziness, mental depression, nausea, vomiting, narcosis, anesthesia, coma.

EYE CONTACT: May cause slight to severe irritation and damage to eye tissues.

SKIN CONTACT: May cause irritation.

INGESTION: Toxic by ingestion. May cause irritation of the gastrointestinal tract, nausea, vomiting, headache, dizziness, mental depression, narcosis, anesthesia, coma. Ingestion of 100 ml has been fatal.

CHRONIC EFFECTS OF OVEREXPOSURE: Possible renal dysfunction or failure, damage to respiratory tract tissues.

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE: Persons with impaired lung function or asthma-like conditions may experience additional breathing difficulties if exposed to vapors. Persons with existing skin disorders may be more susceptible to skin irritation.

OTHER PRECAUTIONS TO CONSIDER: Persons developing hypersensitivity (anaphylactic)-reactions must receive immediate medical attention.

EMERGENCY FIRST AID PROCEDURES:

INHALATION: Remove from exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek immediate medical attention.

EYE CONTACT: Flush immediately with water for at least 15 minutes and seek medical attention.

SKIN CONTACT: Wash thoroughly with soap and water. If irritation persists or develops seek medical attention.

INGESTION: Flush mouth out with water and seek medical attention or contact a poison control center immediately. Do not leave victim unattended.

SECTION 6 - CONTROL AND PROTECTIVE MEASURES

RESPIRATORY PROTECTION: NIOSH/MSHA approved respirator.

PROTECTIVE GLOVES: Chemical resistant gloves.

EYE PROTECTION: Safety goggles. Avoid wearing contact lenses when working with this or any chemical due to the possibility of increased severity of eye damage.

VENTILATION: Local explosion-proof exhaust recommended.

OTHER PROTECTIVE EQUIPMENT: Appropriate laboratory apparel.

HYGIENIC WORK PRACTICES: Do not eat, drink or smoke near this material. Wash thoroughly after handling and wash any contaminated clothing before reuse.

SECTION 7 - HANDLING AND STORAGE PRECAUTIONS

HANDLING PRECAUTIONS: Avoid contact with eyes, skin or clothing and avoid breathing vapors. Wash thoroughly after handling and wash any contaminated clothing before reuse.

STORAGE PRECAUTIONS: Store in a tight container in a cool, dry, well ventilated location away from any ignition sources.

SECTION 8 - SPILL AND DISPOSAL PROCEDURES

STEPS TO BE TAKEN IN CASE OF SPILL OR DISCHARGE: Remove any ignition source and ventilate spill site. Wear all protective gear including: respirator, goggles, gloves. Mop up spillage with an absorbent material and place in a tight container. Wash spill site and remove contaminated absorbent materials. Wash thoroughly or shower after handling and wash all clothing and protective gear before reuse.

WASTE DISPOSAL METHOD: Dispose of in accordance with all applicable local, state, federal, and environmental regulations.

SECTION 9 - DISCLAIMER

The information contained in this Material Safety Data Sheet has been compiled from reliable sources and is believed to be correct as of the date issued. It is the responsibility of the user to determine the appropriateness and applicability to their situation. Paddock Laboratories, Inc. disclaims any expressed or implied warranty as to the accuracy of the above information and shall not be held liable for any direct, incidental, or consequential damages from use or reliance on the above information.

DEFINITIONS OF ABBREVIATIONS USED:

ACGIH: Amer

American Conference of Governmental Industrial Hygienists

CAS:

Chemical Abstract Service

IARC:

Internal Agency for Research on Cancer

IDLH:

Immediately Dangerous to Life or Health level

 LC_{50} :

Median Lethal Concentration

 LD_{50} :

Median Lethal Dose

MSHA:

Mine Safety and Health Administration

N/A:

Not available

NIOSH:

National Institute for Occupational Safety and Health

NTP:

National Toxicology Program

OSHA:

Occupational Safety and Health Administration

PEL: STEL: Permissible Exposure Limit Short Term Exposure Limit

TLV:

Threshold Limit Value

TWA:

Time Weighted Average

ISOPROPYL ALCOHOL 99%

Attachment to Material Safety Data Sheet

TRANSPORTATION INFORMATION

APPLICABLE DOT REGULATIONS: Title 49

SHIPPING NAME: Isopropanol

IDENTIFICATION NUMBER: UN1219

REPORTABLE QUANTITY: Yes (1 gallon per container).

LABELS:

One Gallon: "Flammable Liquid (3) Isopropanol UN1219"

One Pint: "ORM-D Consumer Commodity"

UNIT CONTAINER:

One Gallon: Natural, square, high density polyethylene bottle with a polyethylene coated paper on pulpboard

lined white metal cap.

One Pint:

Natural, oblong, pinched waist, polyethylene alcohol bottle with a foam-lined white polypropylene

cap.

DOT SPECIFICATION CONTAINER:

Bottle:

DOT 2E

Carton: DOT 12-B

DOT EXEMPTION NUMBER: Not available.

DOD CERTIFICATION CONTROL NUMBER: Not available.

NET EXPLOSIVE WEIGHT: Not applicable.

LIMITED QUANTITY: No.

AEROSOL PROPELLANTS: Not applicable.

USPS REGULATIONS: Not available.

DISPOSAL INFORMATION

EPA HAZARDOUS WASTE NUMBER/CODE: Not listed.

HAZARDOUS WASTE CHARACTERISTICS: Highly flammable.

DISPOSAL METHODS: Incineration accordance with all applicable local, state and federal regulations.