NIAGARA® Heavy Spray Starch

Page 1 of 5 Rev. Date 05/07/07

SECTION #1 - PRODUCT AND COMPANY IDENTIFICATION

Product: NIAGARA® Heavy Spray Starch

Phoenix Brands Consumer Service Telephone Number: 1-866-794-0800

2855 N. Franklin Rd., #7 Emergency Contact: PROSAR IPC

Indianapolis, Indiana 46219 USA Emergency Phone Number: 1-866-794-0800

Product Description: Aqueous solution/suspension of starch in pressurized aerosol can.

SECTION #2 - COMPOSITION, INFORMATION ON INGREDIENTS

Product Component: Starch (CAS No. 9005-25-8)

OSHA PEL: 15 mg/m₃ (total dust); 5 mg/m₃ (respirable fraction)

ACGIH TLV: 10 mg/m3

Propellant Component: Isobutane (CAS No. (75-28-5)

OSHA PEL: 1000 parts per million (ppm) TWA, as Liquified Petroleum Gas

ACGIH TLV: 1000 ppm TWA, as Liquified Petroleum Gas

SECTION #3 – HAZARDS IDENTIFICATION

Route of Exposure - Inhalation

Under normal conditions of use, there are no known health hazards from inhalation. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

Route of Exposure - Skin

The constituents are not skin irritants nor are they known to be allergenic.

Route of Exposure - Eyes

The product is non-irritating. Contact with the eyes may produce temporary discomfort due to the presence of foreign objects.

Route of Exposure - Ingestion

The product is non-irritating. Ingestion may cause temporary discomfort in the mouth and upper gastrointestinal tract.

SECTION #4 – FIRST AID MEASURES

First Aid - Inhalation

Give the subject access to fresh air. If symptoms do not resolve quickly, seek medical assistance.

First Aid - Skin

If skin irritation occurs in use, seek medical assistance.

 ${\tt NIAGARA}^{\scriptsize (8)}$ Heavy Spray Starch

Page 2 of 5 Rev. Date 05/07/07

SECTION #4 - FIRST AID MEASURES CONTINUED...

First Aid - Eyes

Flush affected areas with water for at least 15 minutes. Seek medical assistance if required.

First Aid - Ingestion

Treat symptomatically. If the individual is unconscious or convulsive, seek medical assistance.

SECTION #5 – FIRE FIGHTING MEASURES

Propellant: Flash Point: -117°F./-83°C Autoignition Temperature: 860°F./460°C

Lower Explosive Limit: 1.8% Upper Explosive Limit: 8.4%

Fire and Explosion Hazards

Although the contents are non-flammable and non-explosive, the propellant is highly flammable. Do not spray product near an open flame or other source of ignition. Do not expose cans to heat or store at temperatures exceeding 120°F./49°C. Do not puncture or incinerate containers.

Extinguishing Media

See Special Fire Fighting Instructions

Special Fire Fighting Instructions

If containers are endangered by fire from an external source, cool them with water spray to prevent rupture of cans and ignition of the propellant. A fire proximate to large quantities of flammable pressurized cans represents and explosion hazard, and should be controlled only by those with appropriate qualifications and training.

SECTION #6 - ACCIDENTAL RELEASE MEASURES

Steps to be Taken in The Event of Spills, Leaks, or Release

If cans are ruptured, eliminate sources of ignition. Evacuate all non-essential personnel and ventilate the area. Contents of cans may be flushed away with large quantities of water. If covered by product, floors may be slippery.

Waste Disposal Methods

Do not puncture or incinerate containers. Dispose of unused containers of product in accordance with applicable Federal, State/Provincial, and local regulations.

SECTION #7 – HANDLING AND STORAGE

Store cans in a dry place at temperatures below 120°F./49°C. and way from flames and incompatible materials (see Section #10).

NFPA 30B Storage: Level 1

SECTION #8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

NIAGARA® Heavy Spray Starch

Page 3 of 5 Rev. Date 05/07/07

Ventilation

Mechanical ventilation is not required under normal conditions of use.

Eye Protection

Eye protection is not required under normal conditions of use. If eye contact is likely, wear eye protection.

Skin Protection

Skin protection is not normally required. If gloves are desired for protection against irritation, water-impervious types (e.g. rubber, PVA, or nitrile) are recommended.

Respiratory Protection

Respiratory protection is not normally required. If this product is used in a manner that generates airborne mist not controlled by ventilation, wear a NIOSH-approved respirator with filters for protection against dusts (type N95 or better). For guidance on the selection and use of respiratory protection, consult American National Standard Z88.2-1992 (ANSI, New York, NY 10036 USA).

SECTION #9 - PHYSICAL AND CHEMICAL PROPERTIES

Product:Solubility (H₂O): soluble Percent Volatiles: not applicable

Vapor pressure: not applicable Evaporation Rate: not applicable

Appearance: milky translucent aqueous mixture, floral odor

Propellant: Vapor pressure: 31 PSIG at 70F/21C Percent Volatiles: 100%

Boiling Point: 11°F./-12°C Vapor Density (air=1): 2.01 Sp. Gravity (H₂0=1): 0.56 Solubility (H₂O): sparingly

Appearance: colorless gas, mild petroleum odor

SECTION #10 - STABILITY AND REACTIVITY

Conditions to Avoid

This product is stable when maintained at room temperature. If heated to temperatures above 120°F./49°C., cans may rupture.

Incompatible Materials

Cans should not be exposed to mists or acidic, alkaline, or corrosive chemicals in storage or use.

Hazardous Decomposition Products

If the product is consumed by flame, thermal decomposition byproducts may include carbon monoxide, carbon dioxide, and smoke. Hazardous polymerization will not occur.

SECTION #11 - TOXICOLOGICAL INFORMATION

NIAGARA® Heavy Spray Starch

Page 4 of 5 Rev. Date 05/07/07

Carcinogenicity: None of the components of this product are classified as potential or demonstrated human carcinogens by IARC, NTP, or OSHA.

SECTION #12 – ECOLOGICAL INFORMATION

Component (CAS No.)	LD50 (Route/Species)	LC50 (Route/Species)
Starch (9005-25-8)	No data available	No data available
Isobutane (75-28-5)	No data available	57pph/15 min (inhalation/rat)

SECTION #13 – DISPOSAL CONSIDERATIONS

Do not puncture or incinerate containers. Dispose of unused containers of product in accordance with applicable Federal, State/Provincial, and local regulations.

SECTION #14 – TRANSPORTATION INFORMATION

WHMIS Hazard Classification(s): none applicable

International Maritime Class: 2

UN Number: 1950

SECTION #15 - REGULATORY INFORMATION

Controlled Products Regulations (Canada) Information

SARA Title III - Hazard Class(es): None applicable

SARA Title III - Section 313 Supplier Notification: This product contains no chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act (EPCRA) of 1986 and of 40 CFR 372.

SECTION #16 - OTHER INFORMATION - DEFINITON OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these which are commonly used include the following: CAS #: This is the Chemical Abstract Service Number which uniquely identifies each constituent. It is used for computer-related searching. EXPOSURE LIMITS IN AIR: ACGIH – American Conference of Governmental Industrial Hygienists, a professional association which establishes exposure limits. TLV – Threshold Limit Value – an airborne concentration of a substance which represents conditions under which it is generally believed that nearly all workers may be repeatedly exposed without adverse effect. The duration must be considered, including the 8-hour Time Weighted Average (TWA), the 15-minute Short Term Exposure Limit (STEL), and the instantaneous Ceiling Limit. Skin adsorption effects must also be considered.

OSHA – U. S. Occupational Safety and Health Administration. PEL – Permissible Exposure Limit – this exposure value means exactly the same as a TLV, except that it is enforceable by OSHA. NIOSH is the National Institute of Occupational Safety and Health, which is the research arm of the U.S. Occupational Safety and Health Administration (OSHA). NIOSH issues exposure guidelines called Recommended Exposure Levels (RELs). FLAMMABILITY LIMITS IN AIR: Much of the information related to fire and explosion is derived from the National Fire Protection Association (NFPA). LEL – the lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source. UEL – the highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source.

DISCLAIMER OF EXPRESS AND IMPLIED WARRANTIES

NIAGARA® Heavy Spray Starch

Page 5 of 5 Rev. Date 05/07/07

The foregoing data has been compiled from sources that the company, in good faith, believes to be dependable and is accurate and reliable to the best of our knowledge and belief. However, the company cannot make any warranty or representation respecting the accuracy or completeness of the data, and assumes no responsibility for any liability or damages relating thereto or for advising you regarding the protection of your employees or others. Users should make their own tests to determine the applicability of such information or the suitability of any products for specific use.